

# newline

CERTIFIED

**OPTICAL  
BONDING**



Enterprise Level  
Security



Superior  
Touch



Crystalclear  
Image Quality



Maximum  
Viewing Angle



Object  
Recognition



Bonded  
PCAP



Ultra  
Lightweight



Easy  
Installation

## UNMATCHED POWERFUL PCAP WITH ENTERPRISE LEVEL SECURITY

NAOS IP is Newline's premium solution for the corporate workspace. Based on the combination of optical bonding technology and capacitive touch technology this product line features a superior touch experience, crystal clear images and a true maximum viewing angle. This product line comes in a wide variety of sizes and can be easily combined with the Newline 4K wide angle camera with microphone. This versatile premium solution is optimized for Windows and suits any workspace, from huddle room to large meeting room.

NAOS IP can ensure enterprise level security. This solution has no functional Android which makes it safer. You can still benefit from the Newline interactive ecosystem. Simply complete your NAOS IP with a Newline OPS including the Windows bundle of interactive ecosystem tools for a full Newline experience!

Newline NAOS IP is compatible with optional Newline OPS with Newline interactive ecosystem tools for Windows:

CAST

BROADCAST

LAUNCH CONTROL

# NAOS IP

MODEL	TT-5519IP	TT-6519IP	TT-7519IP	TT-8619IP
<b>Display</b>				
Active Screen Size	55"	65"	75"	86"
Backlight type	LED (WCG + Blue light filter)			
Aspect ratio	16:9			
Resolution	3840 x 2160 (4K UHD)			
Display color	1,07 billion			
Brightness	≥400 cd/m²			
Contrast Ratio (Dynamic)	4000:1			
Viewing angle	178°			
Life Time	≥50.000 hours			
<b>Electrical</b>				
Power Consumption (Normal)	≤190 W	≤250 W	≤300 W	≤400 W
Power Consumption (Standby mode)	<0,5 W			
Working Voltage	AC 100-240 V; 50/60 Hz; Max 3,0 A			
<b>Touch</b>				
Surface treatment	Optical Bonding / Anti-glare tempered glass + Anti-fingerprint			
Touch type	Projective Capacitive Touch (P-cap)			
Writing pen	Fine passive pen			
Touch points	Windows 20 points			
<b>Speaker</b>				
Speaker Position	Downward			
Speaker Rated Impedance	6 Ω	8 Ω		
Speaker Max.Power Output	2 x 20 W	2 x 15 W		
<b>Transportation/Storage</b>				
Outline Dimension	1290 x 764 x 73 mm	1509 x 886 x 86 mm	1731 x 1010 x 86 mm	1977 x 1150 x 86 mm
Package size	1417 x 221 x 871 mm	1640 x 1036 x 221 mm	1859 x 1136 x 247 mm	2119 x 1281 x 275 mm
Net weight	28 Kg	36 Kg	49 Kg	60 Kg
Gross weight	38 Kg	46,5 Kg	62 Kg	76 Kg
VESA Mount	400 x 400 mm	600 x 400 mm	800 x 400 mm	800 x 400 mm
<b>IO Ports</b>				
Rear input ports	HDMI 2.0 (4K@60 Hz) x 2; VGA (2K@60 Hz) x 1; USB-B 2.0 (Touch) x 1; VGA audio in (Jack 3,5 mm) x 1; USB-A 2.0 x 1; YPbPr x 1; RS232 (Serial) x 1			
Rear output ports	Line Out (Earphone Jack 3,5 mm) x 1; AV out x 1			
OPS port	Yes, 4K@60 Hz			
<b>Others</b>				
OPS PC	Available			

## newline

### HEAD OFFICE EMEA

Ronda de Poniente, 16,  
Bajo E, 28760, Tres Cantos,  
Madrid, Spain  
TEL: +34 91 052 8834

### BRANCH OFFICE POLAND

Aleje Jerozolimskie 200,  
pokój 322, 02-486,  
Warszawa, Poland  
TEL: +48 533379973

### BRANCH OFFICE GERMANY

Am Münster 36,  
37154 Northeim  
Germany  
TEL: +49 55515889580

### SHOWROOM/OFFICE ITALY

Via Giuseppe Giusti 10  
20068 Peschiera Borromeo - MI  
Italy  
TEL: +39 3351295904

[newline-interactive.com/eu/](http://newline-interactive.com/eu/) [info\\_eu@newline-interactive.com](mailto:info_eu@newline-interactive.com)

Contact Support: [support\\_eu@newline-interactive.com](mailto:support_eu@newline-interactive.com) / Technical Support Hotline: +34 91 804 31 79